



Traverses overview



		Item number	Length of traverse	Floor lowering	Rough	Galvanised	Weight	Outer frame-work adjustment	Clear loading width
Deliverable from store	Closed construction	Platform width 2550 mm							
		100.0150.99996	2542 mm	27 mm	●	○	44 kg	ZB	2471 mm
		Platform width 2480 mm							
		100.0150.99995	2472 mm	27 mm	●	○	44 kg	ZB	2243 mm
		100.0150.99994	2472 mm	27 mm	●	○	44 kg	SAR	2289 mm
	Open construction	Can be individually shortened							
		100.0150.99998	2542 mm	27 mm	●	○	44 kg	–	2328 mm
		Longitudinal installation							
		100.0150.99997	573 mm	27 mm	●	○	9.3 kg	–	–
		Platform width 2480 mm							
Custom made	Basic	Platform width 2480 mm							
		100.0150.99992	2472 mm	27 mm	●	○	44 kg	ZB	2243 mm
	100.0150.99990	2472 mm	27 mm	●	○	44 kg	SAR	2289 mm	
	Can be individually shortened								
	100.0150.99991	2542 mm	27 mm	●	○	44 kg	–	2328 mm	
Custom made	Basic	Platform width 2550 mm							
		100.0100.xxxxx	max. 2542 mm	adaptable	●	●	individually	●	adaptable
	100.0150.xxxxx	max. 2542 mm	adaptable	●	●	individually	●	adaptable	
Light	HR	Platform width 2480 mm							
		100.2150.xxxxx	max. 2480 mm	adaptable	●	●	individually	●	adaptable

HR = Auxiliary framework construction / LT = Longitudinal beam construction / ● = Standard / ○ = Optional / ZB = Lashing bracket construction / SAR = Inclined outer framework

 **More about our anniversary offers:**
+49 (0) 28 74 / 900 79-0

